



PERSPEX® 10 YEAR GUARANTEE

CELL CAST ACRYLIC SHEET - COLOURS

Standard Colours

Perspex International Limited guarantees that PERSPEX® cast acrylic sheet for exterior applications will comply in service with the performance specifications set out by Perspex International Limited in the Appendix hereto for a period of ten years subject to the following conditions:

1. The guarantee period of ten years runs from the date of delivery of the sheet to the customer.
2. The guarantee covers the quality of the sheet as delivered and in particular:
 - 2.1 The sheet must be appropriately stored and transported prior to fabrication and installation.
 - 2.2 High standards of workmanship shall be used in fabrication and installation and Perspex International Limited will not be liable for any failure attributable to poor standards of such workmanship.
 - 2.3 The guarantee does not cover any failure attributable to causes not usually associated with the normal use of PERSPEX® acrylic sheet and in particular does not apply to harm caused by chemical agents, cleaning fluids, unsuitable sealants or decorative materials.
3. Perspex International Limited must be given immediate notice of any complaint. Sufficient evidence of the complaint must be given to Perspex International Limited and those authorised by it must be allowed adequate facilities to substantiate any complaint.
4. If any PERSPEX® shall be shown to Perspex International Limited's satisfaction to have failed to comply with the said performance specifications within the stipulated time limit Perspex International Limited shall replace the failed sheet with an equivalent amount of PERSPEX® or other suitable alternative sheet to be delivered free of charge by Perspex International Limited to a delivery point to be nominated by the customer, but Perspex International Limited shall under no circumstances be responsible for any other damage or loss howsoever arising whether directly or indirectly.
5. Perspex International Limited gives no guarantee or warranty express or implied in relation to PERSPEX® acrylic sheet apart from the guarantee given herein.
6. This guarantee and all the terms thereof shall apply to all deliveries of PERSPEX® supplied by Perspex International Limited until the guarantee is revoked by either of the parties.

Revocation may be effected by either party serving on the other notice in writing to that effect at any time.
Revocation shall not affect deliveries of sheet made prior to the date of revocation which shall continue to be fully covered by the terms of this guarantee.
7. If the customer shall bring any claim under this guarantee it shall produce documentary evidence to Perspex International Limited's satisfaction that the sheet in question is PERSPEX® made by Perspex International Limited.
8. This guarantee document relates to PERSPEX® sheet exposed in Europe.

Appendix

Outdoor ageing behaviour of PERSPEX® coloured cast acrylic sheet:

1. Elastic Modulus

The rigidity of PERSPEX® will remain substantially unchanged in service. This means that the elastic modulus of a sample cut from a section of PERSPEX® will not be less than 2500 MPa as delivered and for ten years after delivery (test method: ISO 178 measured on specimens removed from the exposed PERSPEX® installation).

2. Tensile Strength

PERSPEX® will suffer no unacceptable change in brittleness. This means that the tensile strength as delivered and for ten years after delivery of a sample cut from a section of PERSPEX® will not be less than 50 MPa. (test method: ISO R 527 measured on specimens, removed from the exposed PERSPEX®).

3. Colourfastness

During a ten year outdoor exposure period all coloured surfaces can be expected to exhibit at least some degree of change. Perspex International Limited guarantees that any changes in colour of the PERSPEX® will be so small as to pass undetected by the casual observer).

