



## PERSPEX® 30 YEAR GUARANTEE

### CLEAR CELL CAST ACRYLIC SHEET

#### Clear Sheet

Perspex International Limited guarantees that PERSPEX® clear cast acrylic sheet will comply in service with the performance specifications set out by Perspex International Limited in the Appendix hereto for a period of thirty years subject to the following conditions:

1. The guarantee period of thirty years runs from the date of delivery of the sheet to the customer.
2. The guarantee covers the quality of the sheet as delivered and in particular:
  - 2.1 The sheet must be appropriately stored and transported prior to fabrication and installation.
  - 2.2 High standards of workmanship shall be used in fabrication and installation and Perspex International Limited will not be liable for any failure attributable to poor standards of such workmanship.
  - 2.3 The guarantee does not cover any failure attributable to causes not usually associated with the normal use of PERSPEX® acrylic sheet and in particular does not apply to harm caused by chemical agents, cleaning fluids, unsuitable sealants or decorative materials.
3. Perspex International Limited must be given immediate notice of any complaint. Sufficient evidence of the complaint must be given to Perspex International Limited and those authorised by it must be allowed adequate facilities to substantiate any complaint.
4. If any PERSPEX® shall be shown to Perspex International Limited's satisfaction to have failed to comply with the said performance specifications within the stipulated time limit Perspex International Limited shall replace the failed sheet with an equivalent amount of PERSPEX® or other suitable alternative sheet to be delivered free of charge by Perspex International Limited to a delivery point to be nominated by the customer, but Perspex International Limited shall under no circumstances be responsible for any other damage or loss howsoever arising whether directly or indirectly.
5. Perspex International Limited gives no guarantee or warranty express or implied in relation to PERSPEX® acrylic sheet apart from the guarantee given herein.
6. This guarantee and all the terms thereof shall apply to all deliveries of PERSPEX® supplied by Perspex International Limited until the guarantee is revoked by either of the parties.

Revocation may be effected by either party serving on the other notice in writing to that effect at any time.
7. Revocation shall not affect deliveries of sheet made prior to the date of revocation which shall continue to be fully covered by the terms of this guarantee.
8. If the customer shall bring any claim under this guarantee it shall produce documentary evidence to Perspex International Limited's satisfaction that the sheet in question is PERSPEX® made by Perspex International Limited.

#### Appendix

Outdoor ageing behaviour of PERSPEX® clear cast acrylic sheet:

##### 1. Light transmission

The light transmission for clear PERSPEX® will not fall below 85% (test method: ASTM D 1003 when measured using a cleaned and polished flat sample of 1mm thickness taken from the exposed sheet).

##### 2. Yellowness Index

The yellowness index of clear cast PERSPEX® will not be more than 10 after a period of 30 years, dependent on the application and surrounding environment. This value is measured using a cleaned and polished flat sample in accordance with DIN 5036.

